Model No. VS12915

VA1932wma

48cm/19" VALUE SERIES WIDESCREEN LCD DISPLAY

Super Contrast Ratio Widescreen

- **Fast 5ms video response delivers superior picture clarity**
- **1440 x 900 native resolution**
  Incredible image detail for sharp text and graphics.
- **100,000:1 dynamic contrast ratio typical**
  Provides for darker black levels and better overall front-of-screen performance.
- **Stylish slim-bezel design**
  An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- **OSD/power lock secures your settings**
  Prevents unauthorised changes to monitor settings and maintains your optimised image.
- **OnView® controls for superior screen adjustability**
  Screen adjustments are precisely made via an easy-to-use on-screen menu.
- **Windows 7 approved**
- **Eco modes, to reduce operating power consumption by up to 40%**
- **PC and Mac® compatible**

Model Name:		VA1932wma	VA1932wa
LCD	Size	48cm/19" Wide Color a-Si TFT Active Matrix LCD 16:10 aspect ratio	
	Optimum Resolution	1440 × 900	
	Brightness (cd/m²)	300 (Typical)	
	Contrast Ratio (Typ.)	1,000:1	
	Dynamic Contrast Ratio	100,000:1	
	Viewing Angle (CR≧10 / CR≧5)	170° (V), 160° (V)	
	Response Time (ms)	5 ms	
	Pixel Pitch (H×V)	0.2835 × 0.2835 (mm)	
	Panel Surface	Anti-Glare, Hard coating(3H)	
	Light Source (Hours)	50,000 Minimum	
	Color Support (Millions of colours)	16.7 M	
INPUT	Analog	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)	
	Sync	Separate, composite	
	Frequency (Fh / Fv)	24–82kHz / 50–75Hz	
COMPATIBILITY	PC	VGA up to 1440 × 900 Non Interlaced	
	Mac	Mac OS up to 1440 × 900	
CONNECTOR	Analog	1×15 pin mini D-sub	1×15 pin mini D-sub
	Audio	1×3.5mm Audio In	
	Power	Internal Power Board, 3-pin plug x1	Internal Power Board, 3-pin plug x1
SPEAKER	Speaker	2W x 2	-
POWER	Voltage	AC 100-240V (Universal); 50/60 Hz	AC 100-240V (Universal); 50/60 Hz
	Consumption (W)	40 W Typical, 45 W Maximum	35 W Typical, 40 W Maximum
	Save mode (W)	≦0.5W	≦0.5W
CONTROLS	Basic	[1], [2], [PW], [Dn], [Up]	
	OnView / OSD	Auto Image Adjust, Contrast/Brightness, Audio Adjust (only for VA1932wma)Volume, Mute, Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B] Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Eco mode, Setup Menu, Language Select, Resolution Notice, OSD Position, OSD Time out, OSD Background, Auto Power Off, Memory Recall	
OPERATING CONDITIONS	Temperature	0 - 40 (°C) / 32 - 104 (°F)	
	Humidity (Non condensed)	20 - 90 (%)	
DIMENSIONS (WxHxD)	Physical (w/ stand)	445.2 x 376.0 x 189.4 (mm) / 17.5 x 14.8 x 7.5 (in)	
WEIGHT	Net (w/ stand)	3.42 kg / 7.54 lb	
REGULATIONS		CB, WEEE, RoHS, REACH SVHC List, EuPWindows XP/ Vista Basic, CE, Nemko ERGO, GOST-R+Hygienic, UkrSEPRO, BSMI, PSB, C-TICK, KC, SASO	
WALL MOUNT (mm)	VESA® Mount Complliant	100mm × 100mm	

For more product information, visit us at ap.viewsonic.com

ViewSonic®
See the difference™